



Top View

SOT-23



Product Summary

- V_{DS} 30V
- I_D 3.6A
- $R_{DS(ON)}$ (at $V_{GS}=10V$) <39 mohm
- $R_{DS(ON)}$ (at $V_{GS}=4.5V$) <52mohm

General Description

- Trench Power LV MOSFET technology
- High Power and current handing capability

Applications

- PWM application
- Load switch

■ Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-source Voltage		V_{DS}	30	V
Gate-source Voltage		V_{GS}	± 20	V
Drain Current	$T_A=25^\circ\text{C}$ @ Steady State	I_D	3.6	A
	$T_A=70^\circ\text{C}$ @ Steady State		2.9	
Pulsed Drain Current ^A		I_{DM}	15	A
Total Power Dissipation @ $T_A=25^\circ\text{C}$		P_D	1.0	W
Thermal Resistance Junction-to-Ambient @ Steady State ^B		$R_{\theta JA}$	125	$^\circ\text{C}/\text{W}$
Junction and Storage Temperature Range		T_J, T_{STG}	-55~+150	$^\circ\text{C}$

■ Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static Parameter						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V, I_D=250\mu A$	30			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=30V, V_{GS}=0V, T_C=25^\circ\text{C}$			1	μA
Gate-Body Leakage Current	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$			± 100	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	1.2	1.5	2.2	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V, I_D=3.6A$		30	39	m Ω
		$V_{GS}=4.5V, I_D=3A$		40	52	
Diode Forward Voltage	V_{SD}	$I_S=3.6A, V_{GS}=0V$			1.2	V
Maximum Body-Diode Continuous Current	I_S				3.6	A
Dynamic Parameters						
Input Capacitance	C_{iss}	$V_{DS}=15V, V_{GS}=0V, f=1\text{MHz}$		520		pF
Output Capacitance	C_{oss}			90		
Reverse Transfer Capacitance	C_{rss}			53		
Switching Parameters						
Total Gate Charge	Q_g	$V_{GS}=10V, V_{DS}=15V, I_D=3.6A$		4.2		nC
Gate Source Charge	Q_{gs}			1.0		
Gate Drain Charge	Q_{gd}			1.3		
Turn-on Delay Time	$t_{D(on)}$	$V_{GS}=4.5V, V_{DD}=15V, R_L=3.6\Omega, R_{GEN}=6\Omega$		11		ns
Turn-on Rise Time	t_r			48		
Turn-off Delay Time	$t_{D(off)}$			14		
Turn-off Fall Time	t_f			9		

A. Pulse Test: Pulse Width $\leq 300\mu s$, Duty cycle $\leq 2\%$.

B. Device mounted on FR-4 PCB, 1 inch x 0.85 inch x 0.062 inch.

■ Typical Performance Characteristics




Figure1. Output Characteristics




Figure2. Transfer Characteristics




Figure3. Capacitance Characteristics




Figure4. Gate Charge




Figure5. Drain-Source on Resistance




Figure6. Drain-Source on Resistance




Figure7. Safe Operation Area








Figure8. Switching wave

■SOT-23 Package information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

■SOT-23 Suggested Pad Layout



Note:

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.